

MANITOWOC ENGINEERING CO.

Division of The Manitowoc Company, Inc. Manitowoc, Wisconsin 54220



LIFTCRANE CAPACITIES

BOOM NO. 22 WITH OPEN THROAT TOP
104,400 LB. COUNTERWEIGHT
360 DEGREE RATING

MEETS
ANSI B30.5
REQUIREMENTS

4000W

CAPACITIES FOR VARIOUS BOOM LENGTHS AND OPERATING RADII ARE FOR FREELY SUSPENDED LOADS AND DO NOT EXCEED 75% OF A STATIC TIPPING LOAD. CAPACITIES BASED ON STRUCTURAL COMPETENCE ARE DENOTED BY AN ASTERISK (*).

UPPER BOOM POINT CAPACITY FOR LIFTCRANE SERVICE WITH SINGLE PART WHIP LINE OR COMBINATION OF TWO SINGLE PART LINES IS 28,300 LBS. (20,000 LBS. WHEN REAR AUXILIARY DRUM IS USED). IN ALL CASES, UPPER BOOM POINT CAPACITIES CANNOT EXCEED THOSE LISTED FOR THE MAIN BOOM CAPACITY.

WEIGHT OF UPPER BOOM POINT, JIB, ALL LOAD BLOCKS, HOOKS, WEIGHT BALL, SLINGS, HOIST LINES, ETC., BENEATH BOOM AND JIB POINT SHEAVES, IS CONSIDERED PART OF THE MAIN BOOM LOAD. BOOM IS NOT TO BE LOWERED BEYOND RADII WHERE COMBINED WEIGHTS ARE GREATER THAN RATED CAPACITY. WHERE NO CAPACITY IS SHOWN, OPERATION IS NOT INTENDED OR APPROVED.

MACHINE TO OPERATE IN A LEVEL POSITION ON A FIRM UNIFORMLY SUPPORTING SURFACE WITH GANTRY UP. REFER TO BOOM RIGGING NO. 4816B AND WIRE ROPE SPECIFICATION CHART NO. 6664-A. CRANE OPERATOR JUDGMENT MUST BE USED TO ALLOW FOR DYNAMIC LOAD EFFECTS OF SWINGING, HOISTING OR LOWERING, TRAVEL, WIND CONDITIONS, AS WELL AS ADVERSE OPERATING CONDITIONS AND PHYSICAL MACHINE DEPRECIATION.

OPERATING RADIUS IS THE HORIZONTAL DISTANCE FROM THE AXIS OF ROTATION TO THE CENTER OF VERTICAL HOIST LINE OR LOAD BLOCK. BOOM ANGLE IS THE ANGLE BETWEEN HORIZONTAL AND CENTERLINE OF BOOM BUTT AND INSERTS, AND IS AN INDICATION OF OPERATING RADIUS. IN ALL CASES, OPERATING RADIUS SHALL GOVERN CAPACITY. BOOM POINT ELEVATION IS VERTICAL DISTANCE FROM GROUND LEVEL TO CENTERLINE OF BOOM POINT SHAFT.

MACHINE EQUIPPED WITH 24' EXTENDIBLE CRAWLERS, 48" TREADS, 15' RETRACTABLE GANTRY, 12 PART BOOM HOIST REEVING, FOUR 1-3/8" BOOM PENDANTS, 1ST COUNTERWEIGHT = 40,100 LBS. (39,000 LBS. WITH COUNTERWEIGHT ASSEMBLY NO. 48998), 2ND COUNTERWEIGHT = 35,800 LBS., AND 3RD COUNTERWEIGHT = 28,500 LBS.

MAXIMUM BOOM AND JIB LENGTHS LIFTED UNASSISTED					
OVER END OF BLOCKED CRAWLERS		OVER SIDE OF EXTENDED CRAWLERS		OVER SIDE OF RETRACTED CRAWLERS	
BOOM LGTH.	JIB NO. 123	BOOM LGTH.	JIB NO. 123	BOOM LGTH.	JIB NO. 123
220'	---	200'	---	190'	---
210'	---	190'	---	180'	---
200'	40'	180'	50'	170'	50'
190'	60'	170'	50'	160'	60'

LOAD BLOCK, HOOK AND WEIGHT BALL ON GROUND AT START. UPPER BOOM POINT CANNOT BE USED ON 220' BOOM.

DEDUCT FROM CAPACITIES WHEN UPPER BOOM POINT IS ATTACHED		DEDUCT FROM CAPACITIES WHEN JIB IS ATTACHED	
ONE SHEAVE POINT	TWO SHEAVE POINT	JIB LGTH.	JIB NO. 123
1,200 LBS.	1,500 LBS.	30'	3,000 LBS.
		40'	3,600 LBS.
		50'	4,200 LBS.
		60'	4,900 LBS.

JIB DEDUCTS INCLUDE JIB ADAPTOR.

CONSULT JIB CHART FOR JIB CAPACITIES.

BOOM LGTH. FEET	OPER. RAD. FEET	BOOM ANG. DEG.	BOOM POINT ELEV. FEET	CAPACITY CRAWLERS RETRACTED POUNDS	CAPACITY CRAWLERS EXTENDED POUNDS	BOOM LGTH. FEET	OPER. RAD. FEET	BOOM ANG. DEG.	BOOM POINT ELEV. FEET	CAPACITY CRAWLERS RETRACTED POUNDS	CAPACITY CRAWLERS EXTENDED POUNDS
	15	80.7	76.2	350,000*	350,000*						
	16	79.9	76.0	308,600	332,800*		16	81.1	86.1	308,300	311,000*
	17	79.0	75.8	275,000	307,800*		17	80.4	86.0	274,700	306,300*
	18	78.2	75.6	248,000	285,200*		18	79.7	85.8	247,600	283,800*
	19	77.3	75.4	225,600	270,100*		19	78.9	85.6	225,200	268,800*
	20	76.5	75.2	206,900	253,500*		20	78.2	85.4	206,500	252,600*
	22	74.8	74.7	177,200	214,000		22	76.8	85.0	176,800	213,600
	24	73.1	74.1	154,800	184,800		24	75.3	84.5	154,300	184,400
	26	71.4	73.4	137,200	162,500		26	73.8	83.9	136,700	162,100
	28	69.7	72.7	123,100	144,800		28	72.3	83.3	122,500	144,300
	30	67.9	72.0	111,500	130,500		30	70.8	82.6	110,900	130,000
	32	66.1	71.1	101,700	118,600		32	69.3	81.9	101,200	118,100
	34	64.3	70.2	93,500	108,600		34	67.7	81.1	93,000	108,100
	36	62.5	69.2	86,400	100,100		36	66.2	80.3	85,900	99,600
	38	60.6	68.1	80,300	92,700		38	64.6	79.4	79,700	92,200
	40	58.7	66.9	74,900	86,300		40	63.0	78.4	74,300	85,800
	45	53.8	63.6	63,900	73,400		45	58.9	75.6	63,400	72,900
	50	48.6	59.6	55,600	63,700		50	54.6	72.3	55,000	63,100
	55	42.8	54.7	49,000	56,000		55	50.1	68.5	48,400	55,400
	60	36.4	48.7	43,600	49,800		60	45.2	63.9	43,000	49,200
	65	28.8	40.8	39,200	44,800		65	39.9	58.5	38,600	44,200
	70	18.6	29.5	35,500	40,500		70	34.0	51.8	34,900	39,900
							75	26.9	43.3	31,700	36,300
							80	17.4	31.0	29,000	33,200

CHART NO. 6274-A, 3-22-93/GA
PAGE 1 OF 4

MANITOWOC ENGINEERING CO.

Division of The Manitowoc Company, Inc. Manitowoc, Wisconsin 54220



LIFT CRANE CAPACITIES

BOOM NO. 22 WITH OPEN THROAT TOP
104,400 LB. COUNTERWEIGHT
360 DEGREE RATING

MEETS
ANSI B30.5
REQUIREMENTS

4000W

BOOM LGTH. FEET	OPER. RAD. FEET	BOOM ANG. DEG.	BOOM POINT ELEV. FEET	CAPACITY CRAWLERS RETRACTED POUNDS	CAPACITY CRAWLERS EXTENDED POUNDS	BOOM LGTH. FEET	OPER. RAD. FEET	BOOM ANG. DEG.	BOOM POINT ELEV. FEET	CAPACITY CRAWLERS RETRACTED POUNDS	CAPACITY CRAWLERS EXTENDED POUNDS
9	17	81.5	96.1	267,100	267,100	120	22	81.2	125.7	175,500	186,800
	18	80.8	96.0	247,400	267,100		24	80.2	125.4	153,000	183,400
	19	80.2	95.8	225,000	263,000		26	79.3	125.0	135,300	160,900
	20	79.5	95.6	206,200	250,500		28	78.3	124.6	121,100	143,100
	22	78.2	95.2	176,500	213,400		30	77.3	124.2	109,500	128,700
	24	76.9	94.8	154,000	184,200		32	76.3	123.7	99,700	116,800
	26	75.6	94.3	136,400	161,800		34	75.4	123.2	91,500	106,700
	28	74.3	93.8	122,200	144,100		36	74.4	122.7	84,400	98,200
	30	73.0	93.2	110,600	129,700		38	73.4	122.1	78,200	90,800
	32	71.7	92.5	100,900	117,800		40	72.4	121.5	72,800	84,300
	34	70.3	91.8	92,600	107,800		45	69.9	119.8	61,800	71,400
	36	68.9	91.1	85,500	99,200		50	67.3	117.8	53,400	61,500
	38	67.6	90.3	79,400	91,900		55	64.7	115.6	46,700	53,800
	40	66.2	89.4	74,000	85,500		60	62.0	113.1	41,400	47,600
	45	62.7	87.1	63,000	72,500		65	59.3	110.2	36,900	42,600
	50	59.0	84.3	54,600	62,700		70	56.4	107.1	33,200	38,300
	55	55.2	81.0	48,000	55,100		75	53.5	103.6	30,000	34,700
	60	51.2	77.3	42,700	48,900		80	50.5	99.7	27,300	31,600
65	47.0	73.0	38,200	43,800	85	47.3	95.3	24,900	28,900		
70	42.5	67.9	34,500	39,600	90	44.0	90.5	22,800	26,500		
75	37.6	62.0	31,400	36,000	95	40.4	84.9	21,000	24,400		
80	32.0	54.8	28,600	32,900	100	36.6	78.7	19,300	22,600		
85	25.4	45.6	26,300	30,200	105	32.4	71.4	17,900	20,900		
90	16.4	32.5	24,200	27,800	110	27.6	62.7	16,500	19,400		
110					115	21.9	51.9	15,300	18,000		
100	19	81.2	105.9	224,600	243,000	130	24	81.0	135.5	152,600	183,300
	20	80.6	105.8	205,800	243,000		26	80.1	135.2	135,000	160,600
	22	79.4	105.4	176,100	213,100		28	79.2	134.8	120,800	142,800
	24	78.3	105.0	153,500	183,800		30	78.3	134.4	109,100	128,300
	26	77.1	104.6	135,900	161,400		32	77.4	134.0	99,400	116,400
	28	75.9	104.1	121,800	143,600		34	76.5	133.5	91,100	106,400
	30	74.7	103.6	110,100	129,200		36	75.6	133.0	84,000	97,800
	32	73.5	103.0	100,400	117,300		38	74.7	132.5	77,800	90,400
	34	72.3	102.4	92,100	107,300		40	73.8	131.9	72,400	84,000
	36	71.1	101.7	85,000	98,800		45	71.5	130.4	61,400	71,000
	38	69.9	101.0	78,800	91,400		50	69.1	128.6	53,000	61,100
	40	68.7	100.3	73,400	85,000		55	66.7	126.5	46,300	53,400
	45	65.6	98.2	62,500	72,000		60	64.3	124.3	41,000	47,200
	50	62.4	95.7	54,100	62,200		65	61.8	121.7	36,500	42,100
	55	59.1	92.9	47,400	54,500		70	59.3	118.9	32,800	37,900
	60	55.7	89.7	42,100	48,300		75	56.7	115.8	29,600	34,300
	65	52.2	86.1	37,700	43,300		80	54.0	112.3	26,900	31,200
	70	48.4	81.9	33,900	39,000		85	51.3	108.5	24,500	28,500
75	44.5	77.2	30,800	35,400	90	48.4	104.3	22,400	26,100		
80	40.2	71.7	28,000	32,300	95	45.4	99.6	20,600	24,000		
85	35.6	65.3	25,700	29,600	100	42.2	94.4	18,900	22,100		
90	30.3	57.6	23,600	27,200	105	38.8	88.5	17,400	20,500		
95	24.0	47.8	21,700	25,200	110	35.1	81.9	16,100	19,000		
100	15.6	33.9	20,100	23,300	115	31.1	74.2	14,900	17,600		
120					120	26.5	65.1	13,800	16,400		
125					125	21.0	53.8	12,800	15,200		
110	20	81.5	115.9	205,500	215,900	140	24	80.4	145.6	175,700	212,800
	22	80.4	115.6	185,700	212,800		26	79.3	145.2	153,200	183,500
	24	79.3	115.2	163,200	183,500		28	78.3	144.8	135,600	161,100
	26	78.3	114.8	145,600	161,100		30	77.2	144.4	121,400	143,300
	28	77.2	114.4	121,400	143,300		32	76.1	113.9	109,700	128,900
	30	76.1	113.9	109,700	128,900		34	75.1	113.4	100,000	117,000
	32	75.1	113.4	100,000	117,000		36	74.0	112.8	91,700	107,000
	34	74.0	112.8	91,700	107,000		38	72.9	112.2	84,600	98,400
	36	72.9	112.2	84,600	98,400		40	71.8	111.6	78,500	91,000
	38	71.8	111.6	78,500	91,000		45	70.7	110.9	73,100	84,600
	40	70.7	110.9	73,100	84,600		50	67.9	109.0	62,100	71,600
	45	67.9	109.0	62,100	71,600		55	65.1	106.9	53,700	61,800
	50	65.1	106.9	53,700	61,800		60	62.2	104.4	47,000	54,100
	55	62.2	104.4	47,000	54,100		65	59.2	101.6	41,700	47,900
	60	59.2	101.6	41,700	47,900		70	56.1	98.4	37,200	42,900
	65	56.1	98.4	37,200	42,900		75	52.9	94.9	33,500	38,600
	70	52.9	94.9	33,500	38,600		80	49.6	90.8	30,400	35,000
	75	49.6	90.8	30,400	35,000		85	46.1	86.3	27,600	31,900
80	46.1	86.3	27,600	31,900	90	42.3	81.2	25,300	29,200		
85	42.3	81.2	25,300	29,200	95	38.3	75.3	23,200	26,800		
90	38.3	75.3	23,200	26,800	100	33.9	68.4	21,300	24,700		
95	33.9	68.4	21,300	24,700	105	28.9	60.2	19,700	22,900		
100	28.9	60.2	19,700	22,900	110	22.9	49.9	18,200	21,200		

MANITOWOC ENGINEERING CO.

Division of The Manitowoc Company, Inc. Manitowoc, Wisconsin 54220



LIFTCRANE CAPACITIES

BOOM NO. 22 WITH OPEN THROAT TOP
104,400 LB. COUNTERWEIGHT
360 DEGREE RATING

MEETS
ANSI B30.5
REQUIREMENTS

4000W

BOOM LGTH. FEET	OPER. RAD. FEET	BOOM ANG. DEG.	BOOM POINT ELEV. FEET	CAPACITY CRAWLERS RETRACTED POUNDS	CAPACITY CRAWLERS EXTENDED POUNDS	BOOM LGTH. FEET	OPER. RAD. FEET	BOOM ANG. DEG.	BOOM POINT ELEV. FEET	CAPACITY CRAWLERS RETRACTED POUNDS	CAPACITY CRAWLERS EXTENDED POUNDS
140	26	80.8	145.3	134,500	157,000*	160	105	50.7	130.9	16,000	19,100
	28	80.0	145.0	120,300	142,400		110	48.3	126.7	14,700	17,600
	30	79.2	144.6	108,600	127,900		115	45.9	122.0	13,500	16,200
	32	78.3	144.2	98,900	116,000		120	43.4	117.0	12,400	15,000
	34	77.5	143.8	90,600	105,900		125	40.7	111.4	11,300	13,800
	36	76.6	143.3	83,500	97,300		130	37.9	105.3	10,400	12,800
	38	75.8	142.8	77,300	89,900		135	34.8	98.5	9,600	11,800
	40	75.0	142.3	71,900	83,500		140	31.6	90.8	8,800	10,900
	45	72.8	140.9	60,800	70,500		145	28.0	82.1	8,000	10,100
	50	70.7	139.2	52,400	60,600		150	23.9	71.8	7,300	9,400
	55	68.5	137.4	45,800	52,900		155	18.9	59.0	6,700	8,600
	60	66.3	135.3	40,400	46,700		30	81.1	175.1	107,500	126,200*
	65	64.0	133.0	36,000	41,600		32	80.4	174.7	97,700	114,900
	70	61.7	130.4	32,200	37,300		34	79.7	174.4	89,400	104,800
	75	59.4	127.6	29,100	33,700		36	79.0	174.0	82,300	96,200
	80	57.0	124.5	26,300	30,600		38	78.3	173.6	76,100	88,800
	85	54.5	121.1	23,900	27,900		40	77.7	173.2	70,700	82,400
	90	51.9	117.3	21,800	25,500		45	75.9	172.0	59,600	69,300
95	49.3	113.2	20,000	23,400	50	74.2	170.7	51,200	59,500		
100	46.5	108.7	18,300	21,600	55	72.4	169.2	44,500	51,700		
105	43.6	103.7	16,900	19,900	60	70.6	167.5	39,200	45,500		
110	40.6	98.2	15,500	18,400	65	68.9	165.7	34,700	40,400		
115	37.3	92.0	14,300	17,000	70	67.0	163.6	31,000	36,100		
120	33.8	85.0	13,200	15,800	75	65.2	161.4	27,800	32,500		
125	29.9	76.9	12,200	14,700	80	63.3	159.0	25,100	29,400		
130	25.5	67.4	11,300	13,600	85	61.4	156.4	22,700	26,700		
135	20.3	55.6	10,400	12,700	90	59.5	153.6	20,600	24,300		
150	25	81.4	155.4	134,100	157,000*	95	57.5	150.5	18,700	22,200	
	28	80.7	155.1	119,900	142,000	100	55.5	147.2	17,100	20,300	
	30	79.9	154.8	108,200	127,500	105	53.4	143.6	15,600	18,600	
	32	79.1	154.4	98,500	115,600	110	51.3	139.7	14,200	17,100	
	34	78.3	154.0	90,200	105,500	115	49.1	135.6	13,000	15,800	
	36	77.6	153.6	83,100	96,900	120	46.8	131.1	11,900	14,500	
	38	76.8	153.1	76,900	89,500	125	44.5	126.2	10,900	13,400	
	40	76.0	152.6	71,400	83,100	130	42.0	120.9	10,000	12,300	
	45	74.0	151.3	60,400	70,100	135	39.4	115.0	9,100	11,400	
	50	72.0	149.8	52,000	60,200	140	36.7	108.7	8,300	10,500	
	55	70.0	148.0	45,300	52,500	145	33.8	101.6	7,600	9,700	
	60	67.9	146.1	40,000	46,300	150	30.6	93.6	6,900	8,900	
	65	65.9	144.0	35,500	41,200	155	27.1	84.6	6,200	8,200	
	70	63.8	141.6	31,800	36,900	160	23.1	73.9	5,700	7,500	
	75	61.6	139.1	28,600	33,300	165	18.4	60.7	5,100	6,900	
	80	59.4	136.2	25,900	30,200	32	80.9	184.9	97,300	114,500	
	85	57.2	133.1	23,500	27,500	34	80.3	184.5	89,000	104,400	
	90	54.9	129.8	21,400	25,100	36	79.7	184.2	81,800	95,800	
95	52.5	126.1	19,500	23,000	38	79.0	183.8	75,600	88,400		
100	50.0	122.1	17,900	21,100	40	78.4	183.4	70,200	81,900		
105	47.5	117.7	16,400	19,500	45	76.7	182.3	59,100	68,800		
110	44.9	112.9	15,100	17,900	50	75.1	181.0	50,700	59,000		
115	42.1	107.6	13,800	16,600	55	73.4	179.6	44,000	51,200		
120	39.1	101.8	12,700	15,300	60	71.8	178.1	38,600	45,000		
125	36.0	95.3	11,700	14,200	65	70.1	176.3	34,200	39,900		
130	32.6	88.0	10,800	13,200	70	68.4	174.4	30,400	35,600		
135	28.9	79.6	9,900	12,200	75	66.7	172.4	27,300	32,000		
140	24.6	69.7	9,100	11,300	80	64.9	170.1	24,500	28,800		
145	19.6	57.4	8,400	10,500	85	63.1	167.7	22,100	26,100		
					90	61.3	165.0	20,000	23,700		
160	28	81.3	165.2	119,600	141,700	95	59.5	162.2	18,200	21,600	
	30	80.5	164.9	107,900	127,300	100	57.6	159.2	16,500	19,800	
	32	79.8	164.6	98,100	115,300	105	55.7	155.9	15,000	18,100	
	34	79.1	164.2	89,800	105,200	110	53.8	152.3	13,700	16,600	
	36	78.3	163.8	82,700	96,600	115	51.8	148.5	12,500	15,200	
	38	77.6	163.4	76,500	89,200	120	49.7	144.5	11,300	14,000	
	40	76.9	162.9	71,100	82,800	125	47.6	140.1	10,300	12,800	
	45	75.0	161.7	60,100	69,700	130	45.4	135.3	9,400	11,800	
	50	73.2	160.2	51,600	59,900	135	43.1	130.2	8,500	10,800	
	55	71.3	158.6	45,000	52,200	140	40.8	124.6	7,700	9,900	
	60	69.4	156.9	39,600	45,900	145	38.3	118.6	7,000	9,100	
	65	67.5	154.9	35,200	40,800	150	35.6	111.9	6,300	8,300	
	70	65.5	152.7	31,400	36,600	155	32.8	104.6	5,700	7,600	
	75	63.5	150.3	28,200	32,900	160	29.7	96.3	5,100	7,000	
	80	61.5	147.7	25,500	29,800	165	26.3	86.9	4,500	6,300	
	85	59.4	144.9	23,100	27,100	170	22.5	75.9	4,000	5,800	
	90	57.3	141.8	21,000	24,700	175	17.9	62.3	3,500	5,200	
	95	55.2	138.5	19,200	22,600						
100	53.0	134.9	17,500	20,800							

MANITOWOC ENGINEERING CO.

Division of The Manitowoc Company, Inc. Manitowoc, Wisconsin 54220



LIFTCRANE CAPACITIES

BOOM NO. 22 WITH OPEN THROAT TOP
104,400 LB. COUNTERWEIGHT
360 DEGREE RATING

MEETS
ANSI B30.5
REQUIREMENTS

4000W

BOOM LGTH. FEET	OPER. RAD. FEET	BOOM ANG. DEG.	BOOM POINT ELEV. FEET	CAPACITY CRAWLERS		BOOM LGTH. FEET	OPER. RAD. FEET	BOOM ANG. DEG.	BOOM POINT ELEV. FEET	CAPACITY CRAWLERS	
				RETRACTED POUNDS	EXTENDED POUNDS					RETRACTED POUNDS	EXTENDED POUNDS
109	32	81.4	195.0	96,900	114,100	210	36	81.1	214.6	80,600	94,600
	34	80.8	194.7	88,500	104,000		38	80.6	214.3	74,400	87,200
	36	80.2	194.3	81,400	95,400		40	80.0	213.9	68,900	80,700
	38	79.6	194.0	75,200	88,000		45	78.6	213.0	57,900	67,600
	40	79.0	193.6	69,700	81,500		50	77.3	211.9	49,400	57,700
	45	77.4	192.6	58,700	68,400		55	75.9	210.7	42,700	50,000
	50	75.9	191.4	50,200	58,500		60	74.4	209.4	37,300	43,700
	55	74.3	190.0	43,600	50,800		65	73.0	207.9	32,900	38,600
	60	72.8	188.6	38,200	44,600		70	71.6	206.4	29,100	34,300
	65	71.2	186.9	33,700	39,400		75	70.1	204.6	25,900	30,700
	70	69.6	185.1	30,000	35,100		80	68.7	202.7	23,200	27,500
	75	67.9	183.2	26,800	31,500		85	67.2	200.7	20,800	24,800
	80	66.3	181.1	24,000	28,400		90	65.7	198.5	18,700	22,400
	85	64.7	178.8	21,700	25,700		95	64.2	196.2	16,800	20,300
	90	63.0	176.4	19,600	23,300		100	62.7	193.7	15,200	18,500
	95	61.3	173.7	17,700	21,200		105	61.1	191.0	13,700	16,800
	100	59.5	170.9	16,000	19,300		110	59.6	188.2	12,300	15,300
	105	57.8	167.8	14,500	17,600		115	58.0	185.2	11,100	13,900
	110	56.0	164.6	13,200	16,100		120	56.4	181.9	10,000	12,600
	115	54.1	161.1	12,000	14,700		125	54.7	178.5	9,000	11,500
120	52.2	157.3	10,900	13,500	130	53.0	174.9	8,000	10,400		
125	50.3	153.3	9,900	12,400	135	51.3	171.0	7,200	9,500		
130	48.3	149.0	8,900	11,300	140	49.5	166.8	6,400	8,600		
135	46.3	144.4	8,100	10,300	145	47.7	162.4	5,700	7,800		
140	44.1	139.4	7,300	9,500	150	45.8	157.7	5,000	7,000		
145	41.9	134.1	6,500	8,600	155	43.9	152.7	4,300	6,300		
150	39.6	128.3	5,800	7,900	160	41.9	147.3		5,600		
155	37.2	122.0	5,200	7,200	165	39.8	141.5		5,000		
160	34.6	115.1	4,600	6,500	170	37.6	135.3		4,400		
165	31.9	107.5	4,100	5,900							
170	28.9	98.9		5,300							
175	25.6	89.2		4,700							
180	21.9	77.9		4,200							
200	34	81.3	204.8	88,200	95,500*	220	38	81.0	224.4	73,900	86,800
	36	80.7	204.5	81,000	95,000		40	80.5	224.1	68,500	80,300
	38	80.1	204.1	74,800	87,600		45	79.2	223.2	57,400	67,200
	40	79.5	203.8	69,400	81,100		50	77.8	222.2	48,900	57,300
	45	78.1	202.8	58,300	68,100		55	76.5	221.0	42,200	49,500
	50	76.6	201.7	49,900	58,200		60	75.2	219.8	36,800	43,200
	55	75.1	200.4	43,200	50,400		65	73.8	218.4	32,400	38,100
	60	73.6	199.0	37,800	44,200		70	72.5	216.9	28,600	33,800
	65	72.1	197.5	33,300	39,000		75	71.1	215.2	25,400	30,200
	70	70.6	195.8	29,600	34,800		80	69.7	213.4	22,700	27,000
	75	69.1	194.0	26,400	31,100		85	68.3	211.5	20,300	24,300
	80	67.6	192.0	23,600	28,000		90	66.9	209.5	18,200	21,900
	85	66.0	189.8	21,300	25,300		95	65.5	207.2	16,300	19,800
	90	64.4	187.5	19,200	22,900		100	64.0	204.9	14,600	17,900
	95	62.8	185.0	17,300	20,800		105	62.6	202.4	13,100	16,200
	100	61.2	182.4	15,600	18,900		110	61.1	199.7	11,800	14,700
	105	59.6	179.6	14,100	17,200		115	59.6	196.9	10,600	13,300
	110	57.9	176.5	12,800	15,700		120	58.1	193.8	9,500	12,100
	115	56.2	173.3	11,600	14,300		125	56.5	190.6	8,400	11,000
	120	54.4	169.8	10,500	13,100		130	55.0	187.2	7,500	9,900
125	52.7	166.1	9,400	12,000	135	53.3	183.6	6,600	8,900		
130	50.8	162.2	8,500	10,900	140	51.7	179.8	5,800	8,000		
135	49.0	157.9	7,700	9,900	145	50.0	175.7	5,100	7,200		
140	47.0	153.4	6,900	9,100	150	48.3	171.4	4,400	6,500		
145	45.0	148.6	6,100	8,200	155	46.5	166.8		5,700		
150	43.0	143.4	5,400	7,500	160	44.7	161.9		5,100		
155	40.8	137.9	4,800	6,700	165	42.8	156.7		4,400		
160	38.6	131.8	4,200	6,100							
165	36.2	125.3		5,500							
170	33.7	118.2		4,900							
175	31.1	110.3		4,300							